

# WORKOVER RIG 19 (200 t)



## General Specifications

- **PRINCIPAL PARTICULARS**
- Drilling depth theoretical 4.000 m
- Year of construction 2007
- **MAST**
- Type Cross Energy Technologies
- Type: 118 – 440 K
- Height 36 m
- Hookload 200 t
- Torq. Track (without Top Drive) Tesco
- **SUBSTRUCTURE**
- Clear working height 6,8 m
- Rotary table 27 1/2"
- Passage through substructure 30"
- **DRIVE GROUP**
- Engine type 2 x Detroit Diesel 14.4 L.
- 500 hp @ 2000rpm
- Generator type Volvo Penta. TAD 1641GE
- Generator rating 570 KVA
- **MUD PUMPS**
- Pump type White Star Type: WS- 1000
- Capacity 2 Pumps
- Working pressure 345 bar
- Horsepower rating 2 x 1150 hp
- **MUD SYSTEM**
- Capacity 105 m<sup>3</sup>
- Shale shakers 3 x Fluid Systems 'Black Thunder'
- **BOP EQUIPMENT**
- Annular 13 5/8 – 21 1/4"
- Single BOP \_\_\_\_\_
- Double BOP 13 5/8 – 20 3/4"
- **UNIQUE FEATURES**
- Automatic recording and monitoring of all major drilling parameters.
- Small footprint and soundproofing (90dBA)